Vol. 17(1996), No. 3-4

- J. Szargut, J. Skorek, J. Kozioł: Analysis of the evaporation process in the expansion vessel of a GraNo.yd refrigerator
- P. Furmański: The interaction of thermal radiation with a porous layer in the presence of fluid flow
- M. Banaszkiewicz, D. Kardaś: Two-phase flows in converging-diverging channels the BNL experiment
- A. Ziębik: System analysis in thermal engineering
- W. Gajewski: Ecological aspects of energy conversion
- W. Nowak: A note on the VI International Symposium Heat Exchange and Renewable Energy Sources
- M. E. Poniewski: International Conference on Heat Transfer with Change of Phase *Heat'96*, December 8-10, 1996, Kielce, Poland
- A. Rasmus: The XVI Congress of Thermodynamics

Vol. 18(1997), No. 1-2

- W. Nowak, W. Szaflik.: Calculations of parallel-flow heat exchangers with linear and non-linear variability of heat capacity
- J. Madejski: One-dimensional flashing flow application to continuous blowdown and emergency overflow from boiler steam drums
- J. Wilk: Calculations of thermal power of a high-rotating regenerative heat exchanger
- G. Filipczak: Pool boiling heat transfer to tar-oil-water mixtures
- N. Al.-Khalidy, J. Skorek: Applying the Kalman filter method for solving inverse thermal problems
- T. Chmielniak, W. Wróblewski, S. Dykas: Calculations of water vapour flow with condensation
- J. Madejski, W. Wawszczak: High-speed rotating heat exchangers working in countercurrent sets

Vol. 18(1997), No. 3-4

- M. Trela: Stability of a shear driven liquid film on curved surfaces during flow separation D. Butrymowicz, M. Trela: Investigations of heat transfer on a horizontal finned tube fitted with the drainage strip
- P. Wais, K. Rup: The application of the inverse coefficient problem in heat transfer and fluid flow
- J. Mikielewicz, D. Mikielewicz: Heat transfer of two-phase spray impinging on a hot surface
- T. J. Chmielniak, T. M. Chmielniak: Power optimization of an engine working in a closed Brayton cycle
- T. Bohdal: A simplified method for the determination of void fraction during subcooled boiling in channel flow